




Correlation of Thermal Fluid Cryogenic Model through Implementation with Optimization Software


Ellen Smith & Nathan Andrews
Southwest Research Institute

Presented By
Ellen Smith

Thermal & Fluids Analysis Workshop
TFAWS 2024
August 26-30, 2024
NASA Glenn Research Center
Cleveland, OH




- **Nonprofit**
- **Nearly 3,000 employees**
- **More than 1,300 patents**
- **2.3 million ft² / 204,400 m² of laboratories & offices**
- **Over 1,500 acres / 6.07 km² facility in San Antonio, Texas**
- **45+ *R&D 100* awards**



Hartwig, et al

- **Liquid nitrogen**
- **Vertical stainless steel test section**
- **Mostly in vacuum chamber**
- **Flow Reynolds number of 5,992**
- **Upstream and Downstream thermocouple stations**
- **Upstream and Downstream pressure transducer locations**






Darr, et al, 2016

- **Thermal Desktop is a graphical user interface for the Sinda/Fluint solver implemented in an AutoCAD framework**
- **Thermal Desktop automates complicated geometry calculations and is used for advanced pre- and post-processing capabilities**
- **Sinda/Fluint is a lumped parameter and finite difference solver for 3D thermal and 1D fluid analysis**
- **Aerospace heritage dating back to 1960's**
- **Development originally for NASA, now commercialized by ANSYS**

SINDA/FLUINT model network

The system is discretized into states (nodes, lumps) that exchange mass, momentum, and energy through connections (conductors, paths, ties)






- **CENTAUR (Collection of Engineering Tools for Analyzing Uncertainty and Reliability)**
- **Engine behind SwRI's general purpose probabilistic analysis software, NESSUS**
- **Direct interfacing through Python allows for**
 - **Uncertainty quantification**
 - **Surrogate modeling**
 - **Model calibration**
 - **Optimization solution approaches**





- **3 calibration parameters:**
- **Liquid Temperature**
 - Uncalibrated: 80 K
 - Calibrated: 78 K
- **Ambient Temperature**
 - Uncalibrated: 300 K
 - Calibrated: 280 K
- **Pipe Internal Heat Transfer Multiplier**
 - Uncalibrated: 1
 - Calibrated: 0.35





Correlated model predicts wall temp within 6%

Holding liquid temperature constant at 86 K



Holding ambient temperature constant at 291 K



- **Calibrated model prediction of downstream wall temperature is lacking**
- **Likely due to exclusion of ambient heat transfer coefficient in the calibration parameter set**
- **Emphasizes importance of understanding model sensitivity to parameters and confidence in parameter predictions**

